



# CRF 250 RALLY

## SPECIFICATIONS

|                     |                        |
|---------------------|------------------------|
| Overall (L x W x H) | 2,210 x 900 x 1,425 mm |
| Wheelbase           | 1,455 mm               |
| Ground Clearance    | 270 mm                 |
| Seat Height         | 895 mm                 |
| Curb Weight         | 155 kg                 |
| Caster Angle        | 28.1°                  |
| Trail               | 114 mm                 |

|                    |   |
|--------------------|---|
| Turning Radius     | 2,3 m                                     |
| Engine Type        | Liquid-Cooled, 4-Stroke, Single, DOHC     |
| Displacement       | 249,6 cc                                  |
| Fuel Supply System | PGM-FI (Programmed Fuel Injection System) |
| Bore x Stroke      | 76 mm x 55 mm                             |
| Transmission Type  | Manual, 6-Speed                           |
| Compression Ratio  | 10.7 : 1                                  |

|                |                           |
|----------------|---------------------------|
| Maximum Power  | 18.2 kW/8,500 rpm         |
| Maximum Torque | 22.6 Nm/6,750 rpm         |
| Starter Type   | Electric Starter          |
| Clutch Type    | Wet Multi-Plate Hydraulic |
| Final Drive    | Chain                     |
| Oil Capacity   | 1.8 liters                |
| Fuel Capacity  | 10.1 liters               |

|                  |  |
|------------------|--|
| Fuel Consumption | 34.1 km/L (WMTC mode)  |
| Frame Type       | Steel Twin Tube  |
| Suspension Type  | Front: 43 mm Showa Inverted Fork, 250 mm Stroke<br>Rear: Pro-Link 265 Axle Stroke, Showa Single Tube 40 mm |

|                |   |
|----------------|---|
| Brakes         | Front: 296 mm Floating Wave Disc with Dual-Piston Calipers<br>Rear: 220 mm Wave Disc with Single-Piston Caliper |
| Braking System | Standard Type   |

|                 |  |
|-----------------|--|
| Tire Size       | Front: 3.00 - 21 51P<br>Rear: 120/80 - 18M/C 62P |
| Available Color | Extreme Red<br>Extreme Black                     |

**NEW SPORTY COLOR & TOUGHER LOOK**



**250 cc DOHC ENGINE**  
LIQUID-COOLED, 4-STROKE, 4-VALVE, 6-SPEED WITH PGM-FI ENGINE

Adventure awaits every time you are on the new CRF250Rally. Get ready to discover the real thrill of finding new horizons!



Dual Asymmetry LED Headlight with Floating Wind Screen



Digital Panel Meter



Aluminum Swing Arm & Pro-Link Rear Suspension (Showa)



43 mm Inverted Front Fork (Showa) Floating Wave Disc Brake



Extreme Red



Extreme Black



**#CARI\_AMAN**  
saat naik motor

Gunakan selalu helm, pasang tali pengikat dan kencangkan secara benar.  
Gunakan jaket lengan panjang dan sarung tangan yang dirancang untuk keselamatan dan kenyamanan berkendara.  
Pakai celana panjang yang pas dan nyaman serta gunakan sepatu untuk kestabilan saat kaki berpijak.



**Honda Customer Care**  
1-500-989  
0811-9-500-989  
customer.care@astra-honda.com

we love honda indonesia  
we love honda  
we love honda\_id  
we love honda indonesia

www.astra-honda.com

- Periksa tinggi permukaan oli dan gunakan selalu AHM OIL.
- Periksa rem dan tekanan udara ban.
- Gunakan Honda Genuine Parts, suku cadang asli sepeda motor Honda yang didistribusikan oleh PT Astra Honda Motor.
- Lakukan perawatan teratur di bengkel-bengkel resmi Honda (AHASS).

Distribusi oleh  
**AHM**  
PT Astra Honda Motor

